




TiN-coated HSSE precision drills

EX-(SUS) SERIES

Volume 3



KEY FEATURES: EX-SUS SERIES



● EX-SUS-GDR
485 sizes increments of 0.01 from 2.0-6.0mm

● EX-SUS-GDS
Wide variety of 'in-between' sizes
635 sizes, increments of 0.01 from 0.5-6.0mm

① High performance in stainless steels, low carbon steels, copper, (cast) aluminium

② Vanadium HSS substrate + TiN coating

③ Superior toughness, durability & value for money when coolant-through supply is not possible

④ No center drills needed

RECOMMENDED WORK MATERIALS

The EX-SUS-GDS & EX-SUS-GDR drill line is famous worldwide for its incredible performance in gummy materials like stainless steel. Its high helix and refined X-thinning point geometry yield incredible sharpness which make it the ideal solution for processing soft materials. Available in stub and jobber lengths and in diameter increments of every 0.01 mm.

- No center drills needed. Achieves high accuracy high shearing forces ideal in gummy materials.
- Added heat resistance via 3% Vanadium content yields superior performance to standard High Speed Steel drills.
- Increased hardness and lubricity increases wear resistance thereby extending tool life.
- Over 1.100 sizes available from stock, with diameter tolerances that can replace reaming operations

Applications


- Aluminum Alloy, Cast Aluminum, Low Carbon Steel, **Stainless Steel**.
- In applications where internal coolant supply is not possible the EX-SUS drill is the absolute most cost-effective solution for Stainless Steel.
- Any drilling application where you cannot locate an “in-between” diameter size in anyone else’s drill offering.

	EX-SUS-GDS/GDR 	EX-GDS 	EX-GDR 
Low carbon steel	⊙	○	○
Medium carbon steel	○	⊙	⊙
High carbon steel		⊙	⊙
Alloys steels		⊙	⊙
~35 HRC		⊙	○
35~45 HRC		⊙ / ○*	
45~50 HRC			
50~70 HRC			
Stainless	⊙		
Tool steel		⊙ / ○*	⊙
Cast iron		⊙	⊙
Ductile cast iron		○	○
Copper	⊙		
Aluminium	⊙		○
Alu alloy casting	○	○	○
Titanium alloy			
Inconel		○	
Magnesium alloy		○	○

⊙ Recommended ○ Good * Drilling depth 3D~4D

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61505	0,5	38	3	3
8595051	0,51	38	3	3
8595052	0,52	38	3	3
8595053	0,53	38	3	3
8595054	0,54	38	3,5	3
8595055	0,55	38	3,5	3
8595056	0,56	38	3,5	3
8595057	0,57	38	3,5	3
8595058	0,58	38	3,5	3
8595059	0,59	38	3,5	3
61506	0,6	38	3,5	3
8595061	0,61	38	4	3
8595062	0,62	38	4	3
8595063	0,63	38	4	3
8595064	0,64	38	4	3
8595065	0,65	38	4	3
8595066	0,66	38	4	3
8595067	0,67	38	4	3
8595068	0,68	38	4,5	3
8595069	0,69	38	4,5	3
61507	0,7	38	4,5	3
8595071	0,71	38	4,5	3
8595072	0,72	38	4,5	3
8595073	0,73	38	4,5	3
8595074	0,74	38	4,5	3
8595075	0,75	38	4,5	3
8595076	0,76	38	5	3
8595077	0,77	38	5	3
8595078	0,78	38	5	3
8595079	0,79	38	5	3
61508	0,8	38	5	3
8595081	0,81	38	5	3
8595082	0,82	38	5	3
8595083	0,83	38	5	3
8595084	0,84	38	5	3
8595085	0,85	38	5	3
8595086	0,86	38	5,5	3
8595087	0,87	38	5,5	3
8595088	0,88	38	5,5	3
8595089	0,89	38	5,5	3
61509	0,9	38	5,5	3
8595091	0,91	38	5,5	3
8595092	0,92	38	5,5	3
8595093	0,93	38	5,5	3
8595094	0,94	38	5,5	3


EDP	D	L	l	d
8595095	0,95	38	6	3
8595096	0,96	38	6	3
8595097	0,97	38	6	3
8595098	0,98	38	6	3
8595099	0,99	38	6	3
61510	1	38	6	3
8595101	1,01	38	6	3
8595102	1,02	38	6	3
8595103	1,03	38	6	3
8595104	1,04	38	6	3
8595105	1,05	38	6	3
8595106	1,06	38	6	3
8595107	1,07	39	7	3
8595108	1,08	39	7	3
8595109	1,09	39	7	3
61511	1,1	39	7	3
8595111	1,11	39	7	3
8595112	1,12	39	7	3
8595113	1,13	39	7	3
8595114	1,14	39	7	3
8595115	1,15	39	7	3
8595116	1,16	39	7	3
8595117	1,17	39	7	3
8595118	1,18	39	7	3
8595119	1,19	40	8	3
61512	1,2	40	8	3
8595121	1,21	40	8	3
8595122	1,22	40	8	3
8595123	1,23	40	8	3
8595124	1,24	40	8	3
8595125	1,25	40	8	3
8595126	1,26	40	8	3
8595127	1,27	40	8	3
8595128	1,28	40	8	3
8595129	1,29	40	8	3
61513	1,3	40	8	3
8595131	1,31	40	8	3
8595132	1,32	40	8	3
8595133	1,33	41	8	3
8595134	1,34	41	8	3
8595135	1,35	41	8	3
8595136	1,36	41	8	3
8595137	1,37	41	9	3
8595138	1,38	41	9	3
8595139	1,39	41	9	3

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61514	1,4	41	9	3
8595141	1,41	41	9	3
8595142	1,42	41	9	3
8595143	1,43	41	9	3
8595144	1,44	41	9	3
8595145	1,45	41	9	3
8595146	1,46	41	9	3
8595147	1,47	41	9	3
8595148	1,48	41	9	3
8595149	1,49	41	9	3
61515	1,5	41	9	3
8595151	1,51	42	10	3
8595152	1,52	42	10	3
8595153	1,53	42	10	3
8595154	1,54	42	10	3
8595155	1,55	42	10	3
8595156	1,56	42	10	3
8595157	1,57	42	10	3
8595158	1,58	42	10	3
8595159	1,59	42	10	3
61516	1,6	42	10	3
8595161	1,61	42	10	3
8595162	1,62	42	10	3
8595163	1,63	42	10	3
8595164	1,64	42	10	3
8595165	1,65	42	10	3
8595166	1,66	42	10	3
8595167	1,67	42	10	3
8595168	1,68	42	10	3
8595169	1,69	42	10	3
61517	1,7	42	10	3
8595171	1,71	43	11	3
8595172	1,72	43	11	3
8595173	1,73	43	11	3
8595174	1,74	43	11	3
8595175	1,75	43	11	3
8595176	1,76	43	11	3
8595177	1,77	43	11	3
8595178	1,78	43	11	3
8595179	1,79	43	11	3
61518	1,8	43	11	3
8595181	1,81	43	11	3
8595182	1,82	43	11	3
8595183	1,83	43	11	3
8595184	1,84	43	11	3


EDP	D	L	l	d
8595185	1,85	43	11	3
8595186	1,86	43	11	3
8595187	1,87	43	11	3
8595188	1,88	43	11	3
8595189	1,89	43	11	3
61519	1,9	43	11	3
8595191	1,91	44	12	3
8595192	1,92	44	12	3
8595193	1,93	44	12	3
8595194	1,94	44	12	3
8595195	1,95	44	12	3
8595196	1,96	44	12	3
8595197	1,97	44	12	3
8595198	1,98	44	12	3
8595199	1,99	44	12	3
61520	2	44	12	3
8595201	2,01	44	12	3
8595202	2,02	44	12	3
8595203	2,03	44	12	3
8595204	2,04	44	12	3
8595205	2,05	44	12	3
8595206	2,06	44	12	3
8595207	2,07	44	12	3
8595208	2,08	44	12	3
8595209	2,09	44	12	3
61521	2,1	44	12	3
8595211	2,11	44	12	3
8595212	2,12	44	12	3
8595213	2,13	45	13	3
8595214	2,14	45	13	3
8595215	2,15	45	13	3
8595216	2,16	45	13	3
8595217	2,17	45	13	3
8595218	2,18	45	13	3
8595219	2,19	45	13	3
61522	2,2	45	13	3
8595221	2,21	45	13	3
8595222	2,22	45	13	3
8595223	2,23	45	13	3
8595224	2,24	45	13	3
8595225	2,25	45	13	3
8595226	2,26	45	13	3
8595227	2,27	45	13	3
8595228	2,28	45	13	3
8595229	2,29	45	13	3

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61523	2,3	45	13	3
8595231	2,31	45	13	3
8595232	2,32	45	13	3
8595233	2,33	45	13	3
8595234	2,34	45	13	3
8595235	2,35	45	13	3
8595236	2,36	45	13	3
8595237	2,37	46	14	3
8595238	2,38	46	14	3
8595239	2,39	46	14	3
61524	2,4	46	14	3
8595241	2,41	46	14	3
8595242	2,42	46	14	3
8595243	2,43	46	14	3
8595244	2,44	46	14	3
8595245	2,45	46	14	3
8595246	2,46	46	14	3
8595247	2,47	46	14	3
8595248	2,48	46	14	3
8595249	2,49	46	14	3
61525	2,5	46	14	3
8595251	2,51	46	14	3
8595252	2,52	46	14	3
8595253	2,53	46	14	3
8595254	2,54	46	14	3
8595255	2,55	46	14	3
8595256	2,56	46	14	3
8595257	2,57	46	14	3
8595258	2,58	46	14	3
8595259	2,59	46	14	3
61526	2,6	46	14	3
8595261	2,61	46	14	3
8595262	2,62	46	14	3
8595263	2,63	46	14	3
8595264	2,64	46	14	3
8595265	2,65	46	14	3
8595266	2,66	48	16	3
8595267	2,67	48	16	3
8595268	2,68	48	16	3
8595269	2,69	48	16	3
61527	2,7	48	16	3
8595271	2,71	48	16	3
8595272	2,72	48	16	3
8595273	2,73	48	16	3
8595274	2,74	48	16	3


EDP	D	L	l	d
8595275	2,75	48	16	3
8595276	2,76	48	16	3
8595277	2,77	48	16	3
8595278	2,78	48	16	3
8595279	2,79	48	16	3
61528	2,8	48	16	3
8595281	2,81	48	16	3
8595282	2,82	48	16	3
8595283	2,83	48	16	3
8595284	2,84	48	16	3
8595285	2,85	48	16	3
8595286	2,86	48	16	3
8595287	2,87	48	16	3
8595288	2,88	48	16	3
8595289	2,89	48	16	3
61529	2,9	48	16	3
8595291	2,91	48	16	3
8595292	2,92	48	16	3
8595293	2,93	48	16	3
8595294	2,94	48	16	3
8595295	2,95	48	16	3
8595296	2,96	48	16	3
8595297	2,97	48	16	3
8595298	2,98	48	16	3
8595299	2,99	48	16	3
61530	3	48	16	3
8595301	3,01	50	18	4
8595302	3,02	50	18	4
8595303	3,03	50	18	4
8595304	3,04	50	18	4
8595305	3,05	50	18	4
8595306	3,06	50	18	4
8595307	3,07	50	18	4
8595308	3,08	50	18	4
8595309	3,09	50	18	4
61531	3,1	50	18	4
8595311	3,11	50	18	4
8595312	3,12	50	18	4
8595313	3,13	50	18	4
8595314	3,14	50	18	4
8595315	3,15	50	18	4
8595316	3,16	50	18	4
8595317	3,17	50	18	4
8595318	3,18	50	18	4
8595319	3,19	50	18	4

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61532	3,2	50	18	4
8595321	3,21	50	18	4
8595322	3,22	50	18	4
8595323	3,23	50	18	4
8595324	3,24	50	18	4
8595325	3,25	50	18	4
8595326	3,26	50	18	4
8595327	3,27	50	18	4
8595328	3,28	50	18	4
8595329	3,29	50	18	4
61533	3,3	50	18	4
8595331	3,31	50	18	4
8595332	3,32	50	18	4
8595333	3,33	50	18	4
8595334	3,34	50	18	4
8595335	3,35	50	18	4
8595336	3,36	52	20	4
8595337	3,37	52	20	4
8595338	3,38	52	20	4
8595339	3,39	52	20	4
61534	3,4	52	20	4
8595341	3,41	52	20	4
8595342	3,42	52	20	4
8595343	3,43	52	20	4
8595344	3,44	52	20	4
8595345	3,45	52	20	4
8595346	3,46	52	20	4
8595347	3,47	52	20	4
8595348	3,48	52	20	4
8595349	3,49	52	20	4
61535	3,5	52	20	4
8595351	3,51	52	20	4
8595352	3,52	52	20	4
8595353	3,53	52	20	4
8595354	3,54	52	20	4
8595355	3,55	52	20	4
8595356	3,56	52	20	4
8595357	3,57	52	20	4
8595358	3,58	52	20	4
8595359	3,59	52	20	4
61536	3,6	52	20	4
8595361	3,61	52	20	4
8595362	3,62	52	20	4
8595363	3,63	52	20	4
8595364	3,64	52	20	4


EDP	D	L	l	d
8595365	3,65	52	20	4
8595366	3,66	52	20	4
8595367	3,67	52	20	4
8595368	3,68	52	20	4
8595369	3,69	52	20	4
61537	3,7	52	20	4
8595371	3,71	52	20	4
8595372	3,72	52	20	4
8595373	3,73	52	20	4
8595374	3,74	52	20	4
8595375	3,75	52	20	4
8595376	3,76	54	22	4
8595377	3,77	54	22	4
8595378	3,78	54	22	4
8595379	3,79	54	22	4
61538	3,8	54	22	4
8595381	3,81	54	22	4
8595382	3,82	54	22	4
8595383	3,83	54	22	4
8595384	3,84	54	22	4
8595385	3,85	54	22	4
8595386	3,86	54	22	4
8595387	3,87	54	22	4
8595388	3,88	54	22	4
8595389	3,89	54	22	4
61539	3,9	54	22	4
8595391	3,91	54	22	4
8595392	3,92	54	22	4
8595393	3,93	54	22	4
8595394	3,94	54	22	4
8595395	3,95	54	22	4
8595396	3,96	54	22	4
8595397	3,97	54	22	4
8595398	3,98	54	22	4
8595399	3,99	54	22	4
61540	4	54	22	4
8595401	4,01	66	22	6
8595402	4,02	66	22	6
8595403	4,03	66	22	6
8595404	4,04	66	22	6
8595405	4,05	66	22	6
8595406	4,06	66	22	6
8595407	4,07	66	22	6
8595408	4,08	66	22	6
8595409	4,09	66	22	6

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61541	4,1	66	22	6
8595411	4,11	66	22	6
8595412	4,12	66	22	6
8595413	4,13	66	22	6
8595414	4,14	66	22	6
8595415	4,15	66	22	6
8595416	4,16	66	22	6
8595417	4,17	66	22	6
8595418	4,18	66	22	6
8595419	4,19	66	22	6
61542	4,2	66	22	6
8595421	4,21	66	22	6
8595422	4,22	66	22	6
8595423	4,23	66	22	6
8595424	4,24	66	22	6
8595425	4,25	66	22	6
8595426	4,26	68	24	6
8595427	4,27	68	24	6
8595428	4,28	68	24	6
8595429	4,29	68	24	6
61543	4,3	68	24	6
8595431	4,31	68	24	6
8595432	4,32	68	24	6
8595433	4,33	68	24	6
8595434	4,34	68	24	6
8595435	4,35	68	24	6
8595436	4,36	68	24	6
8595437	4,37	68	24	6
8595438	4,38	68	24	6
8595439	4,39	68	24	6
61544	4,4	68	24	6
8595441	4,41	68	24	6
8595442	4,42	68	24	6
8595443	4,43	68	24	6
8595444	4,44	68	24	6
8595445	4,45	68	24	6
8595446	4,46	68	24	6
8595447	4,47	68	24	6
8595448	4,48	68	24	6
8595449	4,49	68	24	6
61545	4,5	68	24	6
8595451	4,51	68	24	6
8595452	4,52	68	24	6
8595453	4,53	68	24	6
8595454	4,54	68	24	6


EDP	D	L	l	d
8595455	4,55	68	24	6
8595456	4,56	68	24	6
8595457	4,57	68	24	6
8595458	4,58	68	24	6
8595459	4,59	68	24	6
61546	4,6	68	24	6
8595461	4,61	68	24	6
8595462	4,62	68	24	6
8595463	4,63	68	24	6
8595464	4,64	68	24	6
8595465	4,65	68	24	6
8595466	4,66	68	24	6
8595467	4,67	68	24	6
8595468	4,68	68	24	6
8595469	4,69	68	24	6
61547	4,7	68	24	6
8595471	4,71	68	24	6
8595472	4,72	68	24	6
8595473	4,73	68	24	6
8595474	4,74	68	24	6
8595475	4,75	68	24	6
8595476	4,76	70	26	6
8595477	4,77	70	26	6
8595478	4,78	70	26	6
8595479	4,79	70	26	6
61548	4,8	70	26	6
8595481	4,81	70	26	6
8595482	4,82	70	26	6
8595483	4,83	70	26	6
8595484	4,84	70	26	6
8595485	4,85	70	26	6
8595486	4,86	70	26	6
8595487	4,87	70	26	6
8595488	4,88	70	26	6
8595489	4,89	70	26	6
61549	4,9	70	26	6
8595491	4,91	70	26	6
8595492	4,92	70	26	6
8595493	4,93	70	26	6
8595494	4,94	70	26	6
8595495	4,95	70	26	6
8595496	4,96	70	26	6
8595497	4,97	70	26	6
8595498	4,98	70	26	6
8595499	4,99	70	26	6

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments



EDP	D	L	l	d
61550	5	70	26	6
8595501	5,01	70	26	6
8595502	5,02	70	26	6
8595503	5,03	70	26	6
8595504	5,04	70	26	6
8595505	5,05	70	26	6
8595506	5,06	70	26	6
8595507	5,07	70	26	6
8595508	5,08	70	26	6
8595509	5,09	70	26	6
61551	5,1	70	26	6
8595511	5,11	70	26	6
8595512	5,12	70	26	6
8595513	5,13	70	26	6
8595514	5,14	70	26	6
8595515	5,15	70	26	6
8595516	5,16	70	26	6
8595517	5,17	70	26	6
8595518	5,18	70	26	6
8595519	5,19	70	26	6
61552	5,2	70	26	6
8595521	5,21	70	26	6
8595522	5,22	70	26	6
8595523	5,23	70	26	6
8595524	5,24	70	26	6
8595525	5,25	70	26	6
8595526	5,26	70	26	6
8595527	5,27	70	26	6
8595528	5,28	70	26	6
8595529	5,29	70	26	6
61553	5,3	70	26	6
8595531	5,31	72	28	6
8595532	5,32	72	28	6
8595533	5,33	72	28	6
8595534	5,34	72	28	6
8595535	5,35	72	28	6
8595536	5,36	72	28	6
8595537	5,37	72	28	6
8595538	5,38	72	28	6
8595539	5,39	72	28	6
61554	5,4	72	28	6
8595541	5,41	72	28	6
8595542	5,42	72	28	6
8595543	5,43	72	28	6
8595544	5,44	72	28	6


EDP	D	L	l	d
8595545	5,45	72	28	6
8595546	5,46	72	28	6
8595547	5,47	72	28	6
8595548	5,48	72	28	6
8595549	5,49	72	28	6
61555	5,5	72	28	6
8595551	5,51	72	28	6
8595552	5,52	72	28	6
8595553	5,53	72	28	6
8595554	5,54	72	28	6
8595555	5,55	72	28	6
8595556	5,56	72	28	6
8595557	5,57	72	28	6
8595558	5,58	72	28	6
8595559	5,59	72	28	6
61556	5,6	72	28	6
8595561	5,61	72	28	6
8595562	5,62	72	28	6
8595563	5,63	72	28	6
8595564	5,64	72	28	6
8595565	5,65	72	28	6
8595566	5,66	72	28	6
8595567	5,67	72	28	6
8595568	5,68	72	28	6
8595569	5,69	72	28	6
61557	5,7	72	28	6
8595571	5,71	72	28	6
8595572	5,72	72	28	6
8595573	5,73	72	28	6
8595574	5,74	72	28	6
8595575	5,75	72	28	6
8595576	5,76	72	28	6
8595577	5,77	72	28	6
8595578	5,78	72	28	6
8595579	5,79	72	28	6
61558	5,8	72	28	6
8595581	5,81	72	28	6
8595582	5,82	72	28	6
8595583	5,83	72	28	6
8595584	5,84	72	28	6
8595585	5,85	72	28	6
8595586	5,86	72	28	6
8595587	5,87	72	28	6
8595588	5,88	72	28	6
8595589	5,89	72	28	6

Drilling | HSS

3xD

EX-SUS-GDS

Drilling | HSS | 3xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 3xD
- For stainless steel, low carbon steel and cast aluminium
- 635 sizes - from Ø 0,5-6 mm in 0,01 mm increments




EDP	D	L	l	d
61559	5,9	72	28	6
8595591	5,91	72	28	6
8595592	5,92	72	28	6
8595593	5,93	72	28	6
8595594	5,94	72	28	6
8595595	5,95	72	28	6
8595596	5,96	72	28	6
8595597	5,97	72	28	6
8595598	5,98	72	28	6
8595599	5,99	72	28	6
61560	6	72	28	6
61561	6,1	75	31	8
61562	6,2	75	31	8
61563	6,3	75	31	8
61564	6,4	75	31	8
61565	6,5	75	31	8
61566	6,6	75	31	8
61567	6,7	75	31	8
61568	6,8	78	34	8
61569	6,9	78	34	8
61570	7	78	34	8
61571	7,1	78	34	8
61572	7,2	78	34	8
61573	7,3	78	34	8
61574	7,4	78	34	8
61575	7,5	78	34	8
61576	7,6	81	37	8
61577	7,7	81	37	8
61578	7,8	81	37	8
61579	7,9	81	37	8
61580	8	81	37	8
61581	8,1	87	37	10
61582	8,2	87	37	10
61583	8,3	87	37	10
61584	8,4	87	37	10
61585	8,5	87	37	10
61586	8,6	90	40	10
61587	8,7	90	40	10
61588	8,8	90	40	10
61589	8,9	90	40	10
61590	9	90	40	10
61591	9,1	90	40	10
61592	9,2	90	40	10
61593	9,3	90	40	10
61594	9,4	90	40	10

EDP	D	L	l	d
61595	9,5	90	40	10
61596	9,6	93	43	10
61597	9,7	93	43	10
61598	9,8	93	43	10
61599	9,9	93	43	10
61600	10	93	43	10
61601	10,1	100	43	12
61602	10,2	100	43	12
61603	10,3	100	43	12
61604	10,4	100	43	12
61605	10,5	100	43	12
61606	10,6	100	43	12
61607	10,7	104	47	12
61608	10,8	104	47	12
61609	10,9	104	47	12
61610	11	104	47	12
61611	11,1	104	47	12
61612	11,2	104	47	12
61613	11,3	104	47	12
61614	11,4	104	47	12
61615	11,5	104	47	12
61616	11,6	104	47	12
61617	11,7	104	47	12
61618	11,8	104	47	12
61619	11,9	108	51	12
61620	12	108	51	12
43011210	12,1	108	51	16
43011220	12,2	108	51	16
43011230	12,3	108	51	16
43011240	12,4	108	51	16
43011250	12,5	108	51	16
43011260	12,6	108	51	16
43011270	12,7	108	51	16
43011280	12,8	108	51	16
43011290	12,9	108	51	16
43011300	13	108	51	16
43011350	13,5	114	54	16
43011400	14	114	54	16
43011450	14,5	116	56	16
43011500	15	116	56	16
43011550	15,5	118	58	16
43011600	16	118	58	16
43011650	16,5	126	60	20
43011700	17	126	60	20
43011750	17,5	128	62	20

Drilling | HSS

3xD

Drilling | HSS | 3xD




- | | | | | |
|---|--------------------------------|---|---|--------------------------------|
| P ☒ | P ☐ | M ☒ | N ☒ | N ☐ |
| C: ≤0,2% | C: 0,25-0,4% | INOX | Al | Ac,ADC |

[illegible][illegible]

EX-SUS-GDR

Drilling | HSS | 5xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 5xD
- For stainless steel, low carbon steel and cast aluminium
- 485 sizes - from Ø 2-6 mm in 0,01 mm increments




EDP	D	L	I	d
62520	2	56	24	3
8597201	2,01	56	24	3
8597202	2,02	56	24	3
8597203	2,03	56	24	3
8597204	2,04	56	24	3
8597205	2,05	56	24	3
8597206	2,06	56	24	3
8597207	2,07	56	24	3
8597208	2,08	56	24	3
8597209	2,09	56	24	3
62521	2,1	56	24	3
8597211	2,11	56	24	3
8597212	2,12	56	24	3
8597213	2,13	59	27	3
8597214	2,14	59	27	3
8597215	2,15	59	27	3
8597216	2,16	59	27	3
8597217	2,17	59	27	3
8597218	2,18	59	27	3
8597219	2,19	59	27	3
62522	2,2	59	27	3
8597221	2,21	59	27	3
8597222	2,22	59	27	3
8597223	2,23	59	27	3
8597224	2,24	59	27	3
8597225	2,25	59	27	3
8597226	2,26	59	27	3
8597227	2,27	59	27	3
8597228	2,28	59	27	3
8597229	2,29	59	27	3
62523	2,3	59	27	3
8597231	2,31	59	27	3
8597232	2,32	59	27	3
8597233	2,33	59	27	3
8597234	2,34	59	27	3
8597235	2,35	59	27	3
8597236	2,36	59	27	3
8597237	2,37	62	30	3
8597238	2,38	62	30	3
8597239	2,39	62	30	3
62524	2,4	62	30	3
8597241	2,41	62	30	3
8597242	2,42	62	30	3
8597243	2,43	62	30	3
8597244	2,44	62	30	3

EDP	D	L	I	d
8597245	2,45	62	30	3
8597246	2,46	62	30	3
8597247	2,47	62	30	3
8597248	2,48	62	30	3
8597249	2,49	62	30	3
62525	2,5	62	30	3
8597251	2,51	62	30	3
8597252	2,52	62	30	3
8597253	2,53	62	30	3
8597254	2,54	62	30	3
8597255	2,55	62	30	3
8597256	2,56	62	30	3
8597257	2,57	62	30	3
8597258	2,58	62	30	3
8597259	2,59	62	30	3
62526	2,6	62	30	3
8597261	2,61	62	30	3
8597262	2,62	62	30	3
8597263	2,63	62	30	3
8597264	2,64	62	30	3
8597265	2,65	62	30	3
8597266	2,66	65	33	3
8597267	2,67	65	33	3
8597268	2,68	65	33	3
8597269	2,69	65	33	3
62527	2,7	65	33	3
8597271	2,71	65	33	3
8597272	2,72	65	33	3
8597273	2,73	65	33	3
8597274	2,74	65	33	3
8597275	2,75	65	33	3
8597276	2,76	65	33	3
8597277	2,77	65	33	3
8597278	2,78	65	33	3
8597279	2,79	65	33	3
62528	2,8	65	33	3
8597281	2,81	65	33	3
8597282	2,82	65	33	3
8597283	2,83	65	33	3
8597284	2,84	65	33	3
8597285	2,85	65	33	3
8597286	2,86	65	33	3
8597287	2,87	65	33	3
8597288	2,88	65	33	3
8597289	2,89	65	33	3

EX-SUS-GDR

Drilling | HSS | 5xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 5xD
- For stainless steel, low carbon steel and cast aluminium
- 485 sizes - from Ø 2-6 mm in 0,01 mm increments



EDP	D	L	l	d
62529	2,9	65	33	3
8597291	2,91	65	33	3
8597292	2,92	65	33	3
8597293	2,93	65	33	3
8597294	2,94	65	33	3
8597295	2,95	65	33	3
8597296	2,96	65	33	3
8597297	2,97	65	33	3
8597298	2,98	65	33	3
8597299	2,99	65	33	3
62530	3	65	33	3
8597301	3,01	68	36	4
8597302	3,02	68	36	4
8597303	3,03	68	36	4
8597304	3,04	68	36	4
8597305	3,05	68	36	4
8597306	3,06	68	36	4
8597307	3,07	68	36	4
8597308	3,08	68	36	4
8597309	3,09	68	36	4
62531	3,1	68	36	4
8597311	3,11	68	36	4
8597312	3,12	68	36	4
8597313	3,13	68	36	4
8597314	3,14	68	36	4
8597315	3,15	68	36	4
8597316	3,16	68	36	4
8597317	3,17	68	36	4
8597318	3,18	68	36	4
8597319	3,19	68	36	4
62532	3,2	68	36	4
8597321	3,21	68	36	4
8597322	3,22	68	36	4
8597323	3,23	68	36	4
8597324	3,24	68	36	4
8597325	3,25	68	36	4
8597326	3,26	68	36	4
8597327	3,27	68	36	4
8597328	3,28	68	36	4
8597329	3,29	68	36	4
62533	3,3	68	36	4
8597331	3,31	68	36	4
8597332	3,32	68	36	4
8597333	3,33	68	36	4
8597334	3,34	68	36	4


EDP	D	L	l	d
8597335	3,35	68	36	4
8597336	3,36	71	39	4
8597337	3,37	71	39	4
8597338	3,38	71	39	4
8597339	3,39	71	39	4
62534	3,4	71	39	4
8597341	3,41	71	39	4
8597342	3,42	71	39	4
8597343	3,43	71	39	4
8597344	3,44	71	39	4
8597345	3,45	71	39	4
8597346	3,46	71	39	4
8597347	3,47	71	39	4
8597348	3,48	71	39	4
8597349	3,49	71	39	4
62535	3,5	71	39	4
8597351	3,51	71	39	4
8597352	3,52	71	39	4
8597353	3,53	71	39	4
8597354	3,54	71	39	4
8597355	3,55	71	39	4
8597356	3,56	71	39	4
8597357	3,57	71	39	4
8597358	3,58	71	39	4
8597359	3,59	71	39	4
62536	3,6	71	39	4
8597361	3,61	71	39	4
8597362	3,62	71	39	4
8597363	3,63	71	39	4
8597364	3,64	71	39	4
8597365	3,65	71	39	4
8597366	3,66	71	39	4
8597367	3,67	71	39	4
8597368	3,68	71	39	4
8597369	3,69	71	39	4
62537	3,7	71	39	4
8597371	3,71	71	39	4
8597372	3,72	71	39	4
8597373	3,73	71	39	4
8597374	3,74	71	39	4
8597375	3,75	71	39	4
8597376	3,76	75	43	4
8597377	3,77	75	43	4
8597378	3,78	75	43	4
8597379	3,79	75	43	4

Drilling | HSS

5xD

EX-SUS-GDR

Drilling | HSS | 5xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 5xD
- For stainless steel, low carbon steel and cast aluminium
- 485 sizes - from Ø 2-6 mm in 0,01 mm increments




EDP	D	L	I	d
62538	3,8	75	43	4
8597381	3,81	75	43	4
8597382	3,82	75	43	4
8597383	3,83	75	43	4
8597384	3,84	75	43	4
8597385	3,85	75	43	4
8597386	3,86	75	43	4
8597387	3,87	75	43	4
8597388	3,88	75	43	4
8597389	3,89	75	43	4
62539	3,9	75	43	4
8597391	3,91	75	43	4
8597392	3,92	75	43	4
8597393	3,93	75	43	4
8597394	3,94	75	43	4
8597395	3,95	75	43	4
8597396	3,96	75	43	4
8597397	3,97	75	43	4
8597398	3,98	75	43	4
8597399	3,99	75	43	4
62540	4	75	43	4
8597401	4,01	87	43	6
8597402	4,02	87	43	6
8597403	4,03	87	43	6
8597404	4,04	87	43	6
8597405	4,05	87	43	6
8597406	4,06	87	43	6
8597407	4,07	87	43	6
8597408	4,08	87	43	6
8597409	4,09	87	43	6
62541	4,1	87	43	6
8597411	4,11	87	43	6
8597412	4,12	87	43	6
8597413	4,13	87	43	6
8597414	4,14	87	43	6
8597415	4,15	87	43	6
8597416	4,16	87	43	6
8597417	4,17	87	43	6
8597418	4,18	87	43	6
8597419	4,19	87	43	6
62542	4,2	87	43	6
8597421	4,21	87	43	6
8597422	4,22	87	43	6
8597423	4,23	87	43	6
8597424	4,24	87	43	6

EDP	D	L	I	d
8597425	4,25	87	43	6
8597426	4,26	91	47	6
8597427	4,27	91	47	6
8597428	4,28	91	47	6
8597429	4,29	91	47	6
62543	4,3	91	47	6
8597431	4,31	91	47	6
8597432	4,32	91	47	6
8597433	4,33	91	47	6
8597434	4,34	91	47	6
8597435	4,35	91	47	6
8597436	4,36	91	47	6
8597437	4,37	91	47	6
8597438	4,38	91	47	6
8597439	4,39	91	47	6
62544	4,4	91	47	6
8597441	4,41	91	47	6
8597442	4,42	91	47	6
8597443	4,43	91	47	6
8597444	4,44	91	47	6
8597445	4,45	91	47	6
8597446	4,46	91	47	6
8597447	4,47	91	47	6
8597448	4,48	91	47	6
8597449	4,49	91	47	6
62545	4,5	91	47	6
8597451	4,51	91	47	6
8597452	4,52	91	47	6
8597453	4,53	91	47	6
8597454	4,54	91	47	6
8597455	4,55	91	47	6
8597456	4,56	91	47	6
8597457	4,57	91	47	6
8597458	4,58	91	47	6
8597459	4,59	91	47	6
62546	4,6	91	47	6
8597461	4,61	91	47	6
8597462	4,62	91	47	6
8597463	4,63	91	47	6
8597464	4,64	91	47	6
8597465	4,65	91	47	6
8597466	4,66	91	47	6
8597467	4,67	91	47	6
8597468	4,68	91	47	6
8597469	4,69	91	47	6

EX-SUS-GDR

Drilling | HSS | 5xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 5xD
- For stainless steel, low carbon steel and cast aluminium
- 485 sizes - from Ø 2-6 mm in 0,01 mm increments



EDP	D	L	I	d
62547	4,7	91	47	6
8597471	4,71	91	47	6
8597472	4,72	91	47	6
8597473	4,73	91	47	6
8597474	4,74	91	47	6
8597475	4,75	91	47	6
8597476	4,76	96	52	6
8597477	4,77	96	52	6
8597478	4,78	96	52	6
8597479	4,79	96	52	6
62548	4,8	96	52	6
8597481	4,81	96	52	6
8597482	4,82	96	52	6
8597483	4,83	96	52	6
8597484	4,84	96	52	6
8597485	4,85	96	52	6
8597486	4,86	96	52	6
8597487	4,87	96	52	6
8597488	4,88	96	52	6
8597489	4,89	96	52	6
62549	4,9	96	52	6
8597491	4,91	96	52	6
8597492	4,92	96	52	6
8597493	4,93	96	52	6
8597494	4,94	96	52	6
8597495	4,95	96	52	6
8597496	4,96	96	52	6
8597497	4,97	96	52	6
8597498	4,98	96	52	6
8597499	4,99	96	52	6
62550	5	96	52	6
8597501	5,01	96	52	6
8597502	5,02	96	52	6
8597503	5,03	96	52	6
8597504	5,04	96	52	6
8597505	5,05	96	52	6
8597506	5,06	96	52	6
8597507	5,07	96	52	6
8597508	5,08	96	52	6
8597509	5,09	96	52	6
62551	5,1	96	52	6
8597511	5,11	96	52	6
8597512	5,12	96	52	6
8597513	5,13	96	52	6
8597514	5,14	96	52	6


EDP	D	L	I	d
8597515	5,15	96	52	6
8597516	5,16	96	52	6
8597517	5,17	96	52	6
8597518	5,18	96	52	6
8597519	5,19	96	52	6
62552	5,2	96	52	6
8597521	5,21	96	52	6
8597522	5,22	96	52	6
8597523	5,23	96	52	6
8597524	5,24	96	52	6
8597525	5,25	96	52	6
8597526	5,26	96	52	6
8597527	5,27	96	52	6
8597528	5,28	96	52	6
8597529	5,29	96	52	6
62553	5,3	96	52	6
8597531	5,31	101	57	6
8597532	5,32	101	57	6
8597533	5,33	101	57	6
8597534	5,34	101	57	6
8597535	5,35	101	57	6
8597536	5,36	101	57	6
8597537	5,37	101	57	6
8597538	5,38	101	57	6
8597539	5,39	101	57	6
62554	5,4	101	57	6
8597541	5,41	101	57	6
8597542	5,42	101	57	6
8597543	5,43	101	57	6
8597544	5,44	101	57	6
8597545	5,45	101	57	6
8597546	5,46	101	57	6
8597547	5,47	101	57	6
8597548	5,48	101	57	6
8597549	5,49	101	57	6
62555	5,5	101	57	6
8597551	5,51	101	57	6
8597552	5,52	101	57	6
8597553	5,53	101	57	6
8597554	5,54	101	57	6
8597555	5,55	101	57	6
8597556	5,56	101	57	6
8597557	5,57	101	57	6
8597558	5,58	101	57	6
8597559	5,59	101	57	6

Drilling | HSS

5xD

EX-SUS-GDR

Drilling | HSS | 5xD



- First choice in quality and performance
- HSSE drill with TiN coating
- Up to 5xD
- For stainless steel, low carbon steel and cast aluminium
- 485 sizes - from Ø 2-6 mm in 0,01 mm increments




EDP	D	L	l	d
62556	5,6	101	57	6
8597561	5,61	101	57	6
8597562	5,62	101	57	6
8597563	5,63	101	57	6
8597564	5,64	101	57	6
8597565	5,65	101	57	6
8597566	5,66	101	57	6
8597567	5,67	101	57	6
8597568	5,68	101	57	6
8597569	5,69	101	57	6
62557	5,7	101	57	6
8597571	5,71	101	57	6
8597572	5,72	101	57	6
8597573	5,73	101	57	6
8597574	5,74	101	57	6
8597575	5,75	101	57	6
8597576	5,76	101	57	6
8597577	5,77	101	57	6
8597578	5,78	101	57	6
8597579	5,79	101	57	6
62558	5,8	101	57	6
8597581	5,81	101	57	6
8597582	5,82	101	57	6
8597583	5,83	101	57	6
8597584	5,84	101	57	6
8597585	5,85	101	57	6
8597586	5,86	101	57	6
8597587	5,87	101	57	6
8597588	5,88	101	57	6
8597589	5,89	101	57	6
62559	5,9	101	57	6
8597591	5,91	101	57	6
8597592	5,92	101	57	6
8597593	5,93	101	57	6
8597594	5,94	101	57	6
8597595	5,95	101	57	6
8597596	5,96	101	57	6
8597597	5,97	101	57	6
8597598	5,98	101	57	6
8597599	5,99	101	57	6
62560	6	101	57	6
62561	6,1	107	63	8
62562	6,2	107	63	8
62563	6,3	107	63	8
62564	6,4	107	63	8

EDP	D	L	l	d
62565	6,5	107	63	8
62566	6,6	107	63	8
62567	6,7	107	63	8
62568	6,8	113	69	8
62569	6,9	113	69	8
62570	7	113	69	8
62571	7,1	113	69	8
62572	7,2	113	69	8
62573	7,3	113	69	8
62574	7,4	113	69	8
62575	7,5	113	69	8
62576	7,6	119	75	8
62577	7,7	119	75	8
62578	7,8	119	75	8
62579	7,9	119	75	8
62580	8	119	75	8
62581	8,1	125	75	10
62582	8,2	125	75	10
62583	8,3	125	75	10
62584	8,4	125	75	10
62585	8,5	125	75	10
62586	8,6	131	81	10
62587	8,7	131	81	10
62588	8,8	131	81	10
62589	8,9	131	81	10
62590	9	131	81	10
62591	9,1	131	81	10
62592	9,2	131	81	10
62593	9,3	131	81	10
62594	9,4	131	81	10
62595	9,5	131	81	10
62596	9,6	137	87	10
62597	9,7	137	87	10
62598	9,8	137	87	10
62599	9,9	137	87	10
62600	10	137	87	10
62601	10,1	144	87	12
62602	10,2	144	87	12
62603	10,3	144	87	12
62604	10,4	144	87	12
62605	10,5	144	87	12
62606	10,6	144	87	12
62607	10,7	151	94	12
62608	10,8	151	94	12
62609	10,9	151	94	12

Drilling | HSS

5xD


Drilling | HSS | 5xD



- | | | | | |
|---|--------------------------------|---|---|--------------------------------|
| P ☒ | P ☐ | M ☒ | N ☒ | N ☐ |
| C: ≤0,2% | C: 0,25-0,4% | INOX | AI | AC,ADC |

[illegible]

KEY FEATURES: EX-SERIES



● **EX-GDR**
249 sizes, from Ø2 - Ø32 available from stock

① Non-step processing to depth
4-5 times the hole diameter allows this
drill to be used for numerous high speed
applications

② Regular for general application

● **EX-GDS**
193 sizes, from Ø1 - Ø13 available from stock

① Rigid flute form and stub length
enhances efficiency and precision
Most suitable for tapping or
lathe processing

② Stub for general application

RECOMMENDED WORK MATERIALS

The EX-GDS & EX-GDR drill line is famous worldwide for its incredible performance in nearly all material families. From cast iron and hardened alloy steel to manual machines or CNC controls, this drill has the toughness and durability to perform. Available in stub and jobber lengths in a complete stocked size offering.

- No center drills needed. Achieves high accuracy while reducing drill thrust force for longer tool life
- Added hardness versus ordinary HSS, yet exceptional toughness provides exceptional versatility in any application.
- Increased hardness and lubricity increases wear resistance thereby extending tool life.

Applications


- Cast Aluminum, Cast Iron, Carbon Steel, Alloy Steel, Die Steel, Hardened Steel < 45 HRC.
- Proven cost-effective in any application, from small run jobs to large scale production runs.
- Easily reground and recoated by OSG's local Regrind Service.

	EX-SUS-GDS/GDR 	EX-GDS 	EX-GDR 
Low carbon steel	◎	○	○
Medium carbon steel	○	◎	◎
High carbon steel		◎	◎
Alloys steels		◎	◎
~35 HRC		◎	○
35~45 HRC		◎ / ○*	
45~50 HRC			
50~70 HRC			
Stainless	◎		
Tool steel		◎ / ○*	◎
Cast iron		◎	◎
Ductile cast iron		○	○
Copper	◎		
Aluminium	◎		○
Alu alloy casting	○	○	○
Titanium alloy			
Inconel		○	
Magnesium alloy		○	○

◎ Recommended ○ Good * Drilling depth 3D~4D

EX-GDS

Drilling | HSS | 3xD



- HSSE drill with TiN coating
- Up to 3xD
- General purpose
- 193 sizes




Drilling | HSS

3xD

EDP	D	L	I	d
60010	1	38	6	3
60410	1,05	38	6	3
60011	1,1	39	7	3
60411	1,15	39	7	3
60012	1,2	40	8	3
60412	1,25	40	8	3
60013	1,3	40	8	3
60413	1,35	41	9	3
60014	1,4	41	9	3
60414	1,45	41	9	3
60015	1,5	41	9	3
60415	1,55	42	10	3
60016	1,6	42	10	3
60416	1,65	42	10	3
60017	1,7	42	10	3
60417	1,75	43	11	3
60018	1,8	43	11	3
60418	1,85	43	11	3
60019	1,9	43	11	3
60419	1,95	44	12	3
60020	2	44	12	3
60420	2,05	44	12	3
60021	2,1	44	12	3
60421	2,15	45	13	3
60022	2,2	45	13	3
60422	2,25	45	13	3
60023	2,3	45	13	3
60423	2,35	45	13	3
60024	2,4	46	14	3
60424	2,45	46	14	3
60025	2,5	46	14	3
60425	2,55	46	14	3
60026	2,6	46	14	3
60426	2,65	46	14	3
60027	2,7	48	16	3
60427	2,75	48	16	3
60028	2,8	48	16	3
60428	2,85	48	16	3
60029	2,9	48	16	3
60429	2,95	48	16	3
60030	3	48	16	3
60430	3,05	50	18	4
60031	3,1	50	18	4
60431	3,15	50	18	4
60032	3,2	50	18	4

EDP	D	L	I	d
60432	3,25	50	18	4
60033	3,3	50	18	4
60433	3,35	50	18	4
60034	3,4	52	20	4
60434	3,45	52	20	4
60035	3,5	52	20	4
60435	3,55	52	20	4
60036	3,6	52	20	4
60436	3,65	52	20	4
60037	3,7	52	20	4
60437	3,75	52	20	4
60038	3,8	54	22	4
60438	3,85	54	22	4
60039	3,9	54	22	4
60439	3,95	54	22	4
60040	4	54	22	4
60440	4,05	66	22	6
60041	4,1	66	22	6
60441	4,15	66	22	6
60042	4,2	66	22	6
60442	4,25	66	22	6
60043	4,3	68	24	6
60443	4,35	68	24	6
60044	4,4	68	24	6
60444	4,45	68	24	6
60045	4,5	68	24	6
60445	4,55	68	24	6
60046	4,6	68	24	6
60446	4,65	68	24	6
60047	4,7	68	24	6
60447	4,75	68	24	6
60048	4,8	70	26	6
60448	4,85	70	26	6
60049	4,9	70	26	6
60449	4,95	70	26	6
60050	5	70	26	6
60450	5,05	70	26	6
60051	5,1	70	26	6
60451	5,15	70	26	6
60052	5,2	70	26	6
60452	5,25	70	26	6
60053	5,3	70	26	6
60453	5,35	72	28	6
60054	5,4	72	28	6
60454	5,45	72	28	6




- HSSE drill with TiN coating
- Up to 3xD
- General purpose
- 193 sizes



EDP	D	L	l	d
60055	5,5	72	28	6
60455	5,55	72	28	6
60056	5,6	72	28	6
60456	5,65	72	28	6
60057	5,7	72	28	6
60457	5,75	72	28	6
60058	5,8	72	28	6
60458	5,85	72	28	6
60059	5,9	72	28	6
60459	5,95	72	28	6
60060	6	72	28	6
60061	6,1	75	31	8
60062	6,2	75	31	8
60063	6,3	75	31	8
60064	6,4	75	31	8
60065	6,5	75	31	8
60465	6,55	75	31	8
60066	6,6	75	31	8
60466	6,65	75	31	8
60067	6,7	75	31	8
60068	6,8	78	34	8
60069	6,9	78	34	8
60070	7	78	34	8
60071	7,1	78	34	8
60072	7,2	78	34	8
60073	7,3	78	34	8
60473	7,35	78	34	8
60074	7,4	78	34	8
60075	7,5	78	34	8
60475	7,55	81	37	8
60076	7,6	81	37	8
60476	7,65	81	37	8
60077	7,7	81	37	8
60078	7,8	81	37	8
60079	7,9	81	37	8
60080	8	81	37	8
60081	8,1	87	37	10
60082	8,2	87	37	10
60083	8,3	87	37	10
60483	8,35	87	37	10
60084	8,4	87	37	10
60085	8,5	87	37	10
60485	8,55	90	40	10
60086	8,6	90	40	10
60486	8,65	90	40	10


EDP	D	L	l	d
60087	8,7	90	40	10
60088	8,8	90	40	10
60089	8,9	90	40	10
60090	9	90	40	10
60091	9,1	90	40	10
60092	9,2	90	40	10
60492	9,25	90	40	10
60093	9,3	90	40	10
60493	9,35	90	40	10
60094	9,4	90	40	10
60494	9,45	90	40	10
60095	9,5	90	40	10
60495	9,55	93	43	10
60096	9,6	93	43	10
60496	9,65	93	43	10
60097	9,7	93	43	10
60098	9,8	93	43	10
60099	9,9	93	43	10
60499	9,95	93	43	10
60100	10	93	43	10
60101	10,1	100	43	12
60102	10,2	100	43	12
62002	10,25	100	43	12
60103	10,3	100	43	12
62003	10,35	100	43	12
60104	10,4	100	43	12
60105	10,5	100	43	12
62005	10,55	100	43	12
60106	10,6	100	43	12
62006	10,65	104	47	12
60107	10,7	104	47	12
60108	10,8	104	47	12
60109	10,9	104	47	12
62009	10,95	104	47	12
60110	11	104	47	12
60111	11,1	104	47	12
60112	11,2	104	47	12
62012	11,25	104	47	12
60113	11,3	104	47	12
62013	11,35	104	47	12
60114	11,4	104	47	12
60115	11,5	104	47	12
62015	11,55	104	47	12
60116	11,6	104	47	12
60117	11,7	104	47	12

Drilling | HSS | 3xD



- | | | | | | | | | | |
|------------|--------------|------------|------------|------------|------------|------------|------------|------------|------------|
| P ○ | P ● | P ● | P ● | K ● | K ○ | N ○ | S ○ | H ● | H ● |
| C: ≤0,2% | C: 0,25-0,4% | C: ≥0,45% | SCM | GG | GGG | AC,ADC | Ni | 25-35 HRC | 35-45 HRC |

[illegible]



- HSSE drill with TiN coating
- Up to 5xD
- General purpose
- 249 sizes




EDP	D	L	I	d
60520	2	56	24	3
62120	2,05	56	24	3
60521	2,1	56	24	3
62121	2,15	59	27	3
60522	2,2	59	27	3
62122	2,25	59	27	3
60523	2,3	59	27	3
62123	2,35	59	27	3
60524	2,4	62	30	3
62124	2,45	62	30	3
60525	2,5	62	30	3
62125	2,55	62	30	3
60526	2,6	62	30	3
62126	2,65	62	30	3
60527	2,7	65	33	3
62127	2,75	65	33	3
60528	2,8	65	33	3
62128	2,85	65	33	3
60529	2,9	65	33	3
62129	2,95	65	33	3
60530	3	65	33	3
62130	3,05	68	36	4
60531	3,1	68	36	4
62131	3,15	68	36	4
60532	3,2	68	36	4
62132	3,25	68	36	4
60533	3,3	68	36	4
62133	3,35	68	36	4
60534	3,4	71	39	4
62134	3,45	71	39	4
60535	3,5	71	39	4
62135	3,55	71	39	4
60536	3,6	71	39	4
62136	3,65	71	39	4
60537	3,7	71	39	4
62137	3,75	71	39	4
60538	3,8	75	43	4
62138	3,85	75	43	4
60539	3,9	75	43	4
62139	3,95	75	43	4
60540	4	75	43	4
62140	4,05	87	43	6
60541	4,1	87	43	6
62141	4,15	87	43	6
60542	4,2	87	43	6

EDP	D	L	I	d
62142	4,25	87	43	6
60543	4,3	91	47	6
62143	4,35	91	47	6
60544	4,4	91	47	6
62144	4,45	91	47	6
60545	4,5	91	47	6
62145	4,55	91	47	6
60546	4,6	91	47	6
62146	4,65	91	47	6
60547	4,7	91	47	6
62147	4,75	91	47	6
60548	4,8	96	52	6
62148	4,85	96	52	6
60549	4,9	96	52	6
62149	4,95	96	52	6
60550	5	96	52	6
62150	5,05	96	52	6
60551	5,1	96	52	6
62151	5,15	96	52	6
60552	5,2	96	52	6
62152	5,25	96	52	6
60553	5,3	96	52	6
62153	5,35	101	57	6
60554	5,4	101	57	6
62154	5,45	101	57	6
60555	5,5	101	57	6
62155	5,55	101	57	6
60556	5,6	101	57	6
62156	5,65	101	57	6
60557	5,7	101	57	6
62157	5,75	101	57	6
60558	5,8	101	57	6
62158	5,85	101	57	6
60559	5,9	101	57	6
62159	5,95	101	57	6
60560	6	101	57	6
62160	6,05	107	63	8
60561	6,1	107	63	8
62161	6,15	107	63	8
60562	6,2	107	63	8
62162	6,25	107	63	8
60563	6,3	107	63	8
62163	6,35	107	63	8
60564	6,4	107	63	8
62164	6,45	107	63	8

EX-GDR

Drilling | HSS | 5xD



- HSSE drill with TiN coating
- Up to 5xD
- General purpose
- 249 sizes




Drilling | HSS

5xD

EDP	D	L	I	d
60565	6,5	107	63	8
62165	6,55	107	63	8
60566	6,6	107	63	8
62166	6,65	107	63	8
60567	6,7	107	63	8
62167	6,75	113	69	8
60568	6,8	113	69	8
62168	6,85	113	69	8
60569	6,9	113	69	8
62169	6,95	113	69	8
60570	7	113	69	8
62170	7,05	113	69	8
60571	7,1	113	69	8
62171	7,15	113	69	8
60572	7,2	113	69	8
62172	7,25	113	69	8
60573	7,3	113	69	8
62173	7,35	113	69	8
60574	7,4	113	69	8
62174	7,45	113	69	8
60575	7,5	113	69	8
62175	7,55	119	75	8
60576	7,6	119	75	8
62176	7,65	119	75	8
60577	7,7	119	75	8
62177	7,75	119	75	8
60578	7,8	119	75	8
62178	7,85	119	75	8
60579	7,9	119	75	8
62179	7,95	119	75	8
60580	8	119	75	8
62180	8,05	125	75	10
60581	8,1	125	75	10
62181	8,15	125	75	10
60582	8,2	125	75	10
62182	8,25	125	75	10
60583	8,3	125	75	10
62183	8,35	125	75	10
60584	8,4	125	75	10
62184	8,45	125	75	10
60585	8,5	125	75	10
62185	8,55	131	81	10
60586	8,6	131	81	10
62186	8,65	131	81	10
60587	8,7	131	81	10

EDP	D	L	I	d
62187	8,75	131	81	10
60588	8,8	131	81	10
62188	8,85	131	81	10
60589	8,9	131	81	10
62189	8,95	131	81	10
60590	9	131	81	10
62190	9,05	131	81	10
60591	9,1	131	81	10
62191	9,15	131	81	10
60592	9,2	131	81	10
62192	9,25	131	81	10
60593	9,3	131	81	10
62193	9,35	131	81	10
60594	9,4	131	81	10
62194	9,45	131	81	10
60595	9,5	131	81	10
62195	9,55	137	87	10
60596	9,6	137	87	10
62196	9,65	137	87	10
60597	9,7	137	87	10
62197	9,75	137	87	10
60598	9,8	137	87	10
62198	9,85	137	87	10
60599	9,9	137	87	10
62199	9,95	137	87	10
60600	10	137	87	10
62200	10,05	144	87	12
60601	10,1	144	87	12
62201	10,15	144	87	12
60602	10,2	144	87	12
62202	10,25	144	87	12
60603	10,3	144	87	12
62203	10,35	144	87	12
60604	10,4	144	87	12
62204	10,45	144	87	12
60605	10,5	144	87	12
62205	10,55	144	87	12
60606	10,6	144	87	12
62206	10,65	151	94	12
60607	10,7	151	94	12
62207	10,75	151	94	12
60608	10,8	151	94	12
62208	10,85	151	94	12
60609	10,9	151	94	12
62209	10,95	151	94	12



- | | | | | | | | | |
|--------------------------------|---|---|---|---|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| P ☐ | P ☒ | P ☒ | P ☒ | K ☒ | K ☐ | N ☐ | N ☐ | H ☐ |
| C: ≤0,2% | C: 0,25-0,4% | C: ≥0,45% | SCM | GG | GGG | AI | AC,ADC | 25-35 HRC |

[illegible]

CUTTING CONDITIONS

Drilling | Solid | Cutting conditions

EX-SUS-GDS/EX-SUS-GDR

	SUS								Al	AC		Cu		C≤0,2%		
	Austenitic SUS304 SUS200		Martensitic SUS420 SUS440		Ferritic SUS430 SUS405		Precipitation SUS630 SUS631		A5052-7075	AC4C - ADC		C1020 - 2600		CK15 - St40 ~500 N/mm²		
Vc	13 ~ 18 m/min		15 ~ 20 m/min		15 ~ 20 m/min		8 ~ 12 m/min		32 ~ 63 m/min		63 ~ 100 m/min		25 ~ 50 m/min		32 ~ 40 m/min	
Ø	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)
1	4.800	0,02~0,04	5.550	0,02~0,04	5.550	0,01~0,03	3.200	0,01~0,03	15.000	0,02~0,06	25.000	0,02~0,06	12.000	0,01~0,03	10.000	0,02~0,05
2	2.400	0,05~0,07	2.850	0,05~0,07	2.850	0,03~0,05	1.600	0,03~0,05	8.000	0,04~0,12	10.000	0,04~0,12	5.100	0,04~0,06	5.700	0,06~0,09
3	1.600	0,06~0,09	1.900	0,06~0,09	1.900	0,04~0,06	1.100	0,04~0,06	5.300	0,06~0,18	6.700	0,06~0,18	3.400	0,06~0,09	3.850	0,10~0,13
4	1.200	0,08~0,12	1.450	0,08~0,12	1.450	0,06~0,08	800	0,06~0,08	4.000	0,08~0,24	6.400	0,08~0,24	2.550	0,08~0,11	2.900	0,11~0,15
5	950	0,10~0,15	1.150	0,12~0,15	1.150	0,08~0,10	650	0,08~0,10	3.200	0,10~0,30	5.000	0,10~0,30	2.050	0,10~0,13	2.260	0,12~0,18
6	800	0,12~0,18	950	0,15~0,18	950	0,09~0,12	550	0,09~0,12	2.700	0,12~0,36	4.200	0,12~0,36	1.700	0,12~0,15	1.900	0,13~0,19
8	600	0,16~0,24	720	0,20~0,24	720	0,12~0,16	400	0,12~0,16	2.000	0,16~0,45	3.200	0,16~0,45	1.250	0,16~0,20	1.400	0,17~0,24
10	480	0,20~0,28	570	0,25~0,30	570	0,15~0,20	320	0,15~0,20	1.600	0,20~0,55	2.500	0,20~0,55	1.000	0,20~0,25	1.120	0,20~0,28
12	400	0,24~0,34	480	0,30~0,36	480	0,18~0,24	280	0,18~0,24	1.350	0,24~0,66	2.100	0,24~0,66	850	0,24~0,30	950	0,24~0,34
13	370	0,26~0,36	440	0,32~0,40	440	0,20~0,26	250	0,20~0,26	1.250	0,25~0,72	2.000	0,25~0,72	780	0,26~0,32	880	0,26~0,36
14	340	0,28~0,39	410	0,35~0,45	410	0,21~0,30	225	0,21~0,30	1.140	0,27~0,74	1.850	0,27~0,74	730	0,26~0,34	820	0,27~0,39
15	320	0,29~0,40	380	0,36~0,48	380	0,22~0,31	210	0,22~0,31	1.060	0,29~0,80	1.700	0,29~0,80	680	0,26~0,36	760	0,28~0,42
16	300	0,30~0,43	355	0,37~0,50	355	0,23~0,32	200	0,23~0,32	1.000	0,30~0,83	1.600	0,30~0,83	640	0,27~0,37	720	0,29~0,43
17	280	0,31~0,45	335	0,38~0,52	335	0,24~0,34	185	0,24~0,34	940	0,31~0,88	1.500	0,31~0,88	600	0,28~0,39	675	0,30~0,46
18	265	0,32~0,47	320	0,39~0,54	320	0,25~0,36	175	0,25~0,36	885	0,32~0,94	1.450	0,32~0,94	570	0,29~0,41	640	0,32~0,49
19	250	0,33~0,48	300	0,40~0,55	300	0,25~0,38	170	0,25~0,38	840	0,34~0,97	1.350	0,34~0,97	540	0,30~0,43	600	0,33~0,51
20	240	0,34~0,50	285	0,40~0,56	285	0,26~0,40	160	0,26~0,40	800	0,36~1,00	1.300	0,36~1,00	510	0,30~0,44	570	0,34~0,52

CUTTING CONDITIONS

Drilling | Solid | Cutting conditions

EX-GDS

	1.05Low Carbon Steel-Mild steel S15C-SS400 ~500N/mm ²		Carbon steel S50c 500~700N/mm ²		Alloy steel SCM-SCr 710~900N/mm ²		Special alloy steel-hardened steel			
							SKD61 ~900N/mm ²		SKD11 900~1060N/mm ²	
Vc	32~40m/min		22~30m/min		20~25m/min		10~16m/min		8~12m/min	
Ø	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)
1	11.500	0,03~0,05	8.000	0,03~0,05	7.000	0,03~0,05	4.000	0,03~0,05	3.200	0,03~0,05
2	5.700	0,06~0,09	4.000	0,06~0,09	3.500	0,06~0,09	2.000	0,06~0,09	1.600	0,06~0,09
3	3.800	0,1~0,13	2.800	0,1~0,13	2.400	0,1~0,13	1.350	0,1~0,13	1.060	0,1~0,13
4	2.900	0,11~0,15	2.100	0,11~0,15	1.800	0,11~0,15	1.000	0,11~0,15	800	0,11~0,15
5	2.300	0,12~0,18	1.650	0,12~0,18	1.400	0,12~0,18	800	0,12~0,18	640	0,12~0,18
6	1.900	0,13~0,19	1.400	0,13~0,19	1.200	0,13~0,19	660	0,13~0,19	530	0,13~0,19
7	1.650	0,15~0,22	1.200	0,15~0,22	1.050	0,15~0,22	570	0,15~0,22	450	0,15~0,22
8	1.400	0,17~0,24	1.050	0,17~0,24	920	0,17~0,24	500	0,16~0,24	400	0,17~0,24
9	1.250	0,18~0,26	920	0,18~0,26	810	0,18~0,26	440	0,18~0,26	350	0,18~0,26
10	1.150	0,20~0,28	830	0,20~0,28	730	0,20~0,28	400	0,20~0,28	230	0,20~0,28
11	1.050	0,22~0,32	750	0,22~0,32	670	0,22~0,32	360	0,22~0,31	300	0,22~0,32
12	950	0,24~0,34	690	0,24~0,34	610	0,24~0,34	330	0,24~0,34	270	0,24~0,34
13	880	0,26~0,36	640	0,26~0,36	560	0,26~0,36	300	0,26~0,36	250	0,26~0,36

	Hardened steel				Inconel 718 38~43HRC		Cast iron FC250 ~350N/mm²		Aluminium alloy casting ADC-AC	
	34~43HRC 1060~1400N/mm²		43~48HRC 1400~1600N/mm²							
Vc	10~15m/min		6~10m/min		6~8m/min		32~40m/min		63~100m/min	
Ø	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)
1	3.800	0,01~0,03	2.500	0,01~0,02	2.500	0,01~0,02	10.000	0,04~0,06	20.000	0,06~0,09
2	1.900	0,02~0,05	1.250	0,02~0,04	1.250	0,02~0,04	5.700	0,08~0,11	10.000	0,12~0,18
3	1.250	0,03~0,08	850	0,03~0,06	850	0,03~0,06	3.800	0,11~0,16	10.000	0,18~0,26
4	960	0,04~0,1	640	0,04~0,08	630	0,04~0,08	2.900	0,13~0,19	7.500	0,24~0,34
5	760	0,05~0,13	510	0,05~0,10	500	0,05~0,10	2.300	0,16~0,22	6.300	0,28~0,40
6	640	0,06~0,15	430	0,06~0,12	430	0,06~0,12	1.900	0,19~0,26	5.000	0,34~0,48
7	550	0,07~0,18	360	0,07~0,14	360	0,07~0,14	1.650	0,20~0,28	4.450	0,36~0,50
8	480	0,08~0,20	320	0,08~0,16	320	0,08~0,16	1.450	0,21~0,31	4.000	0,38~0,53
9	430	0,09~0,23	280	0,09~0,18	280	0,09~0,18	1.270	0,23~0,33	3.450	0,41~0,58
10	380	0,10~0,25	260	0,10~0,20	260	0,10~0,20	1.150	0,25~0,35	3.150	0,45~0,63
11	350	0,11~0,28	230	0,11~0,22	230	0,11~0,22	1.050	0,27~0,38	2.850	0,48~0,69
12	320	0,12~0,30	210	0,12~0,24	210	0,12~0,24	960	0,30~0,42	2.650	0,53~0,75
13	300	0,13~0,32	200	0,13~0,26	200	0,13~0,26	880	0,31~0,42	2.400	0,56~0,79

EX-GDR

	1.05Low Carbon Steel-Mild steel S15C-SS400 ~500N/mm ²		Carbon steel S50c 500~700N/mm ²		Alloy steel SCM-SCr 710~900N/mm ²		Special alloy steel-hardened steel				Cast iron FC250 ~350N/mm ²		Aluminium alloy casting ADC-AC	
							SKD61 ~900N/mm ²		SKD11 900~1060N/mm ²					
Vc	32~40m/min		22~30m/min		20~25m/min		10~16m/min		8~12m/min		32~40m/min		63~100m/min	
Ø	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)	S (min ⁻¹)	F (mm/rev.)
2	5.700	0,06~0,09	4.000	0,06~0,09	3.500	0,06~0,09	1.900	0,06~0,09	1.600	0,06~0,09	5.700	0,08~0,11	10.000	0,12~0,18
3	3.850	0,1~0,13	2.800	0,1~0,13	2.400	0,1~0,13	1.320	0,1~0,13	1.060	0,1~0,13	3.850	0,11~0,16	10.000	0,20~0,28
4	2.900	0,11~0,15	2.100	0,11~0,15	1.800	0,11~0,15	950	0,11~0,15	800	0,11~0,15	2.900	0,13~0,19	7.500	0,24~0,34
5	2.260	0,12~0,18	1.600	0,12~0,18	1.400	0,12~0,18	750	0,12~0,18	630	0,12~0,18	2.260	0,16~0,22	6.300	0,28~0,40
6	1.900	0,13~0,19	1.320	0,13~0,19	1.180	0,13~0,19	630	0,13~0,19	530	0,13~0,19	1.900	0,19~0,26	5.000	0,34~0,48
8	1.400	0,17~0,24	1.000	0,17~0,24	900	0,17~0,24	480	0,17~0,24	400	0,17~0,24	1.400	0,21~0,30	4.000	0,38~0,53
10	1.120	0,20~0,28	800	0,20~0,28	710	0,20~0,28	380	0,20~0,28	320	0,20~0,28	1.120	0,25~0,35	3.150	0,45~0,63
12	950	0,24~0,34	670	0,24~0,34	600	0,24~0,34	320	0,24~0,34	270	0,24~0,34	950	0,30~0,42	2.650	0,53~0,75
13	880	0,26~0,36	610	0,26~0,36	540	0,26~0,36	290	0,26~0,36	240	0,26~0,36	880	0,31~0,42	2.400	0,56~0,79
14	820	0,28~0,39	570	0,28~0,39	500	0,28~0,39	270	0,28~0,39	230	0,28~0,39	820	0,32~0,44	2.250	0,57~0,81
16	720	0,30~0,43	500	0,30~0,43	440	0,30~0,43	240	0,30~0,43	200	0,30~0,43	720	0,34~0,46	1.950	0,61~0,85
18	640	0,34~0,49	440	0,34~0,49	390	0,34~0,49	210	0,34~0,49	180	0,34~0,49	640	0,36~0,50	1.750	0,63~0,90
20	570	0,36~0,50	400	0,36~0,50	350	0,36~0,50	190	0,36~0,50	160	0,36~0,50	570	0,40~0,56	1.550	0,68~0,98
22	520	0,40~0,55	360	0,40~0,55	320	0,40~0,55	170	0,40~0,55	150	0,40~0,55	520	0,42~0,59	1.400	0,73~1,06
24	480	0,41~0,60	330	0,41~0,60	290	0,41~0,60	160	0,41~0,60	135	0,41~0,60	480	0,46~0,65	1.300	0,77~1,13
26	440	0,42~0,65	310	0,42~0,65	270	0,42~0,65	150	0,42~0,65	120	0,42~0,65	440	0,47~0,68	1.200	0,81~1,20
28	410	0,45~0,70	290	0,45~0,70	250	0,45~0,70	140	0,45~0,70	110	0,45~0,70	410	0,50~0,73	1.100	0,84~1,26
30	380	0,48~0,75	270	0,48~0,75	230	0,48~0,75	130	0,48~0,75	105	0,48~0,75	380	0,54~0,78	1.000	0,87~1,32
32	360	0,51~0,80	250	0,51~0,80	220	0,51~0,80	120	0,51~0,80	100	0,51~0,80	360	0,58~0,83	950	0,9~1,38



shaping your dreams

OSG EUROPE LOGISTICS

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord - Belgium
Tel: +32 10 23 05 07
Fax: +32 10 23 05 51
info@osgeurope.com

OSG POLAND Sp. z o.o.

ul. Spółdzielcza 57
05-074 Halinów - Poland
Tel: +22 760 82 71
Fax: +22 760 82 71
osg@osg-poland.com

OSG TURKEY

Rami Kışla Cad.No:56 Eyüp
Istanbul 34056 - Turkey
Tel:+90 212 565 24 00
Fax: +90 212 565 44 00
info@osg-turkey.com

OSG BELUX

Avenue Lavoisier 1
B-1300 Z.I. Wavre - Nord - Belgium
Tel: +32 10 23 05 11
Fax: +32 10 23 05 31
info@osg-belgium.com

OSG GERMANY

Karl-Ehmann-Str. 25
D - 73037 Göppingen - Germany
Tel: +49 7161 6064 - 0
Fax: +49 7161 6064 - 444
info@osg-germany.de

ROMSAN INTERNATIONAL CO. SRL

Reprezentant Exclusiv OSG
23-25, Nerva Traian Street
031044 Bucuresti - România
Tel: +40 021 322 07 47
Fax: +40 021 321 56 00
romsan.int@romsan.ro

OSG FRANCE

Parc Icade, Paris Nord 2
Immeuble "Le Rimbaud"
22 Avenue des Nations
CS66191 - 93420 Villepinte - France
Tel: +33 1 49 90 10 10
Fax: +33 1 49 90 10 15
sales@osg-france.com

OSG SCANDINAVIA

(For Scandinavian countries)
Langebjergvaenget 16
4000 Roskilde - Denmark
Tel: +45 46 75 65 55
Fax: +45 46 75 67 00
osg@osg-scandinavia.com

AUSTRIA

Branch office of OSG GERMANY
Messestraße 11
A-6850 Dornbirn
Tel: +49 7161 6064-0
Fax: +49 7161 6064-444
info@osg-germany.de

OSG NETHERLANDS

Bedrijfsweg 5 - 3481 MG Harmelen
Tel: +31 348 44 2764
Fax: +31 348 44 2144
info@osg-nl.com

SWEDEN

Branch office of OSG SCANDINAVIA
Abrahams Gränd 8
295 35 Bromölla - Sweden
Tel: +46 40 41 22 55
Fax: +46 40 41 32 55
osg@osg-scandinavia.com

OSG ITALIA

Via Cirenica n. 52 int. 61/63
I - 10142 Torino - Italy
Tel: +39 0117705211
Fax: +39 0117071402
info@osg-italia.it

OSG UK

Shelton house, 5 Bentalls
Pipps Hill Ind Est, Basildon Essex SS14 3BY
Tel: +44 845 305 1066
Fax: +44 845 305 1067
sales@osg-uk.com

OSG COMAHER

Bekolarra 4
E - 01010 Vitoria-Gasteiz - Spain
Tel: +34 945 242 400
Fax: +34 945 228 883
osg-comaher@osg-comaher.com

WEXO PRÄZISIONSWERKZEUGE GmbH

Siemensstraße 13
D-61352 Bad Homburg
Tel: (06172) 10 62 06
Fax: (06172) 10 62 13
verkauf@wexo.com

SLOVAKIA

Branch office of OSG Europe Logistics s.a.
Tel (SK) +421 2 4329 1295
Tel (BE) +32 10 23 05 07
Fax (BE) +32 10 23 05 51
sales-osgsvk@osgeurope.com

RUSSIA

Butlerova street, 17B, office 5069
117342 Moscow - Russia
Tel: +7 (495) 150 41 54
info@osg-russia.com

OSG EUROPE LOGISTICS S.A.

08/2017 - All rights reserved. © OSG Europe 2017.

The contents of this catalogue are provided to you for viewing only. They are not intended for reproduction either in part or in whole in this or other medium. They cannot be copied, used to create derivation work or used for any reason, by means without the express, written permission of the copyright owner. If prices are stated, they are netto unit-prices and any eventual tax(es) have to be added. The company is not responsible for any printing error in technical, price and/or any other data.

Tool specifications subject to change without notice.

www.osgeurope.com